

HEATING AND COOLING SOLUTIONS

Over 60 Years of Air Conditioning Innovations



Built into the indoor unit (XE Series), nanoe™ X patented air purification technology is effective in neutralizing common, unpleasant odors while helping to inhibit pollen, mold, bacteria and viruses. It helps provide a fresher and cleaner indoor environment.



Blue Fin Condenser

Blue Fin 3-layer anti-rust coating is applied to each fin. This special coating prevents rust from salt air and moisture from rain and melting snow and assures longer life of the heat exchanger.



High-percision sensor technology allows efficient, automatic operation to match room conditions. This keeps everyone comfortable while saving energy.

Single-Zone	Model Number	Btu/h	Key Features		
	XE9WKUA	9,000	ClimaPure™ XE provides exceptional features and operation.		
	XE12WKUA	12,000	 nanoe™ X patented air purification technology. Operation temperatures down to -15°F for cold climate operation. 		
	XE15WKUA	15,000	Base pan heater included. Auxillary heater connection.		
	XE18WKUA	18,000	 Built-in WiFi connects to Panasonic control app. Commonly specified where rebate programs apply. 		
	XE24WKUA	24,000	Wireless controller is included and wired controller is an available option.		
	E9RKUA	9,000	Exterios E is a verstile line of energy efficient heat pumps. • Indoor units installed with single or multi zone outdoor condenser units.		
	E12RKUA	12,000	Operating temperatures down to -5°F commonly installed in cold climate zones. SEER up to 23 and ENERGY STAR (except 24K).		
(a) 1	E18RKUA	18,000	 Commonly specified where rebate programs apply. ECONAVI sensor adjusts to occupancy and vacancy. Wireless controller is included and a wired controller is an available option. Optional WiFi device and Building Automation connectivity. 		
	E24RKUA	24,000			
	RE9SKUA	9,000	RE Pro Series is an exceptional value line of heat pumps.		
	RE12SKUA	12,000	Panasonic manufacturing with of all Panasonic quality assurances.		
	RE18SKUA	18,000	 16 SEER models provide quality, energy efficiency and value. Operates at -5°F. 		
	RE24SKUA	24,000	Wired controller optional.		
261	YE9WKU1	9,000	YE Pro Series is an exceptional 115V line of heat pumps.		
	YE12WKU1	12,000	• 20 SEER and -13°F operation.		
	KE30NKU	30,000	Big Air wall mounted units provide higher capacities for large residential rooms		
	KE36NKU	36,000	or light commercial. • Ideal for restaurant, medical office, office building lobby, retail stores.		
	KS30NKUA	30,000	 These units are offered as KE Heat Pump models and KS Cooling Only models. Wireless controller is included and a wired controller is available as an option. 		
	KS36NKUA	36,000	Optional WiFi connectivity.		
	E12RB4U	12,000	4-Way Ceilling Cassette ceiling insert for low profile flush-to-ceiling appearance. • 4-way direction air flow.		
	E18RB4U	18,000	 Wireless controller is included and a wired controller is an available option. Optional WiFi device and Building Automation connectivity. 		
	E9SD3UA	9,000	Slim Duct units are designed for low-profile hidden applications. • Install in a ceiling/floor, attic or closet with a minimal duct port to room and		
	E12SD3UA	12,000	a decorative grille. • Operating temperatures down to -5°F.		
	E18SD3UA	18,000	 Wireless controller is included and a wired controller is an available option Optional WiFi device and Building Automation connectivity. 		

Multi-Zones Control of the Control o								
Outdoor L	nits	Btu/h	Indoor Unit C	Options	Btu/h			
2 Zone	Rend Carlo	18,000		CS-ME5RKUA	5,000			
				CS-ME7RKUA	7,000			
				CS-E9RKUAW	9,000			
				CS-E12RKUAW	12,000			
2 – 3 Zone	Primate Grand	19,000		CS-E18RKUAW	18,000			
				CS-E24RKUAW	24,000			
				CS-ME9SB4U	9,000			
2 – 4 Zone	American Services of the Control of	24,000		CS-E12RB4UW	12,000			
				CS-E18RB4UW	18,000			
				CS-ME5SD3UA	5,000			
				CS-ME7SD3UA	7,000			
	Parameter of the state of the s	36,000		CS-E9SD3UAW	9,000			
2 – 5 Zone				CS-E12SD3UAW	12,000			
				CS-E18SD3UAW	18,000			

Professional Series: Resid							
Outdoor L	Btu/h						
	U-26PE1U6	26,000					
	U-36PE1U6	36,000					
	U-42PE1U6	42,000					

PAC Series provides larger capacity options for residential and light commercial spaces including:

- ECONAVI sensor technology option automatially adjusts to occupancy and vacancy providing efficiency and convenience for the user.
- Wired and wireless contollers (sold separately).
- Optional control via WiFi.
- Communication with Panasonic's ECOi VRF system.





www.ahridirectory.org











Serving the U.S. ductless market since 1983